



Urbanscape Green Roof Specs

Size	Green roll: 20mm x 1m x 6m (6m ²) <u>OR</u> 40mm x 1m x 3m (3m ²) Drainage system: 12.5mm x 1m x 12m (12m ²) Root membrane: 0.5m x 4m x 25m (100m ²)
Weight	Dry: 17.9Kg/m ² – 20.1Kg/m ² Saturated: 42.9Kg/m ² – 57.1Kg/m ² *includes an average sedum mat weight
Water Capacity	25l – 37l
Material	Green roll: 100% virgin long rock mineral wool fibres, needled Drainage system: non-woven geotextile bonded to recycled high impact polystyrene Root membrane: black LD Polyethylene
Sedum Mat	The type of sedum mat and plant selection is up to the discretion of the client. We recommend Sedum Masters – Sedum Solutions for Green Roof Applications.
Irrigation System	An irrigation system is always recommended but not required for the Urbanscape system. Should you wish to install one, procurement and sourcing is the responsibility of the client.
Edging	Edging is not necessary in all situations. If your situation requires edging, we recommend Permaloc Corporation – Aluminum Landscape Edging and Restraints.
Ballasts and Pavers	Ballasts, stones and/or pavers are only required in non-vegetated areas of the roof. Procurement of these products are up to client discretion.
Delivery	We will work with you to deliver the green roll, drainage system and root membrane on your selected installation date.
Installation	The installation of the Urbanscape system must be performed by an experienced installer. The installer must completely follow the Urbanscape Installation Guide. It is strongly recommended that installation is done in spring or autumn.
Maintenance	For proper maintenance of the Urbanscape system, we recommend securing a maintenance contract with a green roof maintenance company. At the very least, the Urbanscape maintenance recommendations should be adhered to.

